

i-SENSYS X 1238P Series

PRODUCTIVITY

- Intuitive control with either 5-line LCD or 5" colour touchscreen display
- Fast print speeds
- Double-sided printing as standard
- Customisable display with Application Library

SECURITY

- Embedded user authentication safeguards device access
- Secure Print prevents unauthorised viewing of printed material
- Verify System at Start-up enhances device integrity

CONNECTIVITY

- Support for Apple Air Print and Mopria
- Compatible with Google Cloud Print and the Canon PRINT Business app
- Print directly from USB
- Streamline print processes with uniFLOW Online software*

COMPACT DESIGN

- Small footprint and weight allow for any office configuration
- Add additional cassettes for enhanced input capacity without compromising on device size
- All-in-one space saving toner cartridge lasts for longer

CONTROL AND MAINTENANCE

- Flexible user management solutions for business administrators and IT department
- Remote access to device control functions
- Toner status tool reduces downtime

*Available with the i-SENSYS X 1238P only

QUICK FACTS

i-SENSYS X 1238Pr

- 5-line LCD display
- Print Speed: 38ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- Network, USB and Wi-Fi connectivity
- Max paper input capacity: 900 sheets

i-SENSYS X 1238P

- 5-inch/12.7cm TFT LCD touchscreen
- Print Speed: 38ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- Network, USB, Wi-Fi, and QR code connectivity
- uniFLOW compatibility
- Max paper input capacity: 900 sheets

SERVICES

CORE

Perform routine office operations safely and with ease, utilising embedded software including uniFLOW Online Express and other available services offering complete device maintenance and support



HARDWARE



SOFTWARE



SERVICES

BESPOKE

Choose a tailored service to suit your business needs by removing unnecessary print management burdens. Consult with Canon experts about your specific requirements to find a fitting Print Managed Services option

ENHANCED

Expand cloud capabilities with uniFLOW Online, Canon's all-in-one print management system

TECHNICAL SPECIFICATIONS

i-SENSYS X 1238P Series

PRINTER ENGINE

Print speed	Single sided: Up to 38 ppm (A4) Up to 63.1 ppm(A5-Landscape) Double sided : Up to 31.9 ipm (A4)
Printing method	Monochrome laser beam printing
Print resolution	Up to 1200 x 1200 dpi
Warm-up time	Approx. 14 seconds or less from power on
First Page Out Time	Approx: 5.5 seconds or less
Recommended Monthly Print Volume	750 - 4,000 pages per month
Duty cycle	80,000 pages
Print margins	5 mm-top, bottom, left and right
Advanced printing features	Secure Print Print from USB memory key (JPEG/TIFF/PDF) Barcode Print ¹ Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android: Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app

MEDIA HANDLING

Paper input (Standard)	250-sheet cassette 100-sheet multi-purpose tray
Paper input (Option)	550-sheet cassette
Paper output	150-sheet
Media types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope
Media sizes	Cassette (Standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscape, 16K, Custom sizes: Min. 105 x 148 mm Max. 216.0 x 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscape, 16K, Indexcard, Envelope (COM10, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 216.0 x 355.6 mm.
Media weights	Cassette (standard and optional): 60 to 120 g/m ² Multi-purpose tray: 60 to 163 g/m ²
Double sided printing	A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscape Custom size - Min. 210 x 279.4 mm Max. 216.0 x 355.6 mm 60 to 120 g/m ²

GENERAL FEATURES

Power requirements	220-240V(±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1,330 W Standby: Approx. 9 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 0.33 kWh/week ² For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx
Noise level	Sound Pressure ² : Active: 54 dB Standby: Inaudible ³ Sound Power ² : Active: 68 dB Standby: Inaudible ³

Dimensions (W x D x H)

Weight

Operating environment

Control panel

CONTROLLER

Processor Speed

Memory

Printer Languages

Fonts

Interface and connectivity

Software and Printer Management

i-SENSYS X 1238P: 438 mm x 373 mm x 312 mm i-SENSYS X 1238Pr: 401 mm x 373 mm x 250 mm	i-SENSYS X 1238P: Approx. 9.2 Kg i-SENSYS X 1238Pr: Approx. 8.8 Kg
Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)	i-SENSYS X 1238P: 12.7 cm LCD Colour Touch Screen i-SENSYS X 1238Pr: 5 Line LCD, 3 LED (Job, Error, Energy saver), Buttons, 10-key numeric keypad
800MHz x 2	1GB
UFRII, PCL 5e ⁴ , PCL6, Adobe® PostScript3	93 PCL fonts, 136 PS fonts
USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection	i-SENSYS X 1238P: Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager / uniFLOW online / uniFLOW online Express / uniFLOW compatibility / Application Library
Operating Systems Compatibility	i-SENSYS X 1238Pr: Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Windows® 10 / Windows® 8.1 / Windows® 7 / Server® 2019 / Server® 2016 / Server® 2012R2 / Server® 2012 / Server® 2008R2 / Server® 2008 Mac OS X version 10.9.5 & up / Mac OS 10.15 & up Linux ⁵

CONSUMABLES

All-in-One cartridges

ACCESSORIES/ OPTIONS

Items

TONER T08 (11,000 pages ⁶)	i-SENSYS X 1238P: Cassette Feeding Module-AH1 Barcode Printing Kit-E1E
	i-SENSYS X 1238Pr: Cassette Feeding Module-AH1 MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) MiCard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW) MiCard Attachment kit-B1 Barcode Printing Kit-E1E

Notes:

- ^[1] Accessory - Barcode Printing Kit-E1E - is required
- ^[2] Declared noise emission in accordance with ISO 9296
- ^[3] Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779
- ^[4] A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.
- ^[5] Web distribution only. Driver will be available from second half 2020 onwards.
- ^[6] Based on ISO/IEC 19752
- ^[7] As per US ENERGY STAR® version3.0.